| <b>ADMINISTRATIVE</b> | (to be comp | pleted by the lo | ocal flood plair | n administrator) |
|-----------------------|-------------|------------------|------------------|------------------|
|-----------------------|-------------|------------------|------------------|------------------|

| NOTE: The following is to be completed by the local flood plain administrator. All references to elevation are in feet mean set level (m.s.l.). The term base flood elevation means the same as the 100 year elevation.   |
|---|
| Is the proposed development located in an identified floodway; a flood hazard area where base flood elevations exist with no identified floodway; an area outside of an identified floodway?  |
| NOTE: Floodway development must demonstrate through hydrologic and hydraulic analysis, performed in accordance with standard engineering practice, that no increase in base flood elevation will result during occurrence of the base flood discharge. If base flood elevations exist with no floodway delineation, hydrologic and hydraulic analysis is required to demonstrate not more than one foot increase at any point to the water surface elevation of the base flood. |
| 6. Does proposed development meet NFIP and local General Standards? Construction materials and methods resistant to flood damage Anchored properlyUtilities safe from flooding Subdivision designed to minimize flood damage  Specific Standards? Encroachments - proposed action will not obstruct flood waters Lowest floor elevated to or above base flood elevation Lowest floor floodproofed above base flood elevation  |
| 7. Base flood elevation (100 year) at proposed site: feet m.s.l.  Data Source: Map Effective Date:  |
| 8. Does the structure contain abasement;enclosed area used only for parking access or storage, other than basement, below the lowest floor?   |
| 9. For structures located in unnumbered A zones (no base flood elevation available), the structure's lowest floor is feet above the highest grade adjacent to the structure.  |
| 10. The certified as-build elevation of the structure's lowest floor is feet above m.s.l.*  |
| 11. The certified as-build floodproofed elevation of the structure's lowest floor is feet above m.s.l.*   |
| NOTE: *Certificates of a registered engineer or land surveyor documenting these elevations are necessary if elevations are provided by the applicant.   |
| The proposed development is in compliance with applicable floodplain standards. PERMIT ISSUED ON  |
| The proposed development is <u>not</u> in compliance with applicable floodplain standards.  PERMIT DENIED ON  REASON:   |
| NOTE: All structures must be built with the lowest floor, including the basement, elevated or floodproofed to or above the base flood elevation (100 year) unless a variance has been granted. Only non-residential structures may be floodproofed.   |
| The proposed development is an accessory structure and is <u>exempt</u> from the floodplain standards per Section 5.2-3 of the Flood Damage Prevention Resolution Journal 43 at Page 492.   |
| DATE:Administrator's Signature:   |